



Land Rover Discovery II Maintenance Checklist

extinctmotorsports.com

Vehicle / VIN:

Mileage:

Weekly

Serviced (date / mi):

- Check oil and coolant level.
- Check battery posts for corrosion.

5,000 miles

Serviced (date / mi):

- Oil and filter - 15W-40 diesel engine oil, for the high zinc and detergent content. Wix 51515 or 51068, or Motorcraft FL1A.
- Remove the driveshaft and lubricate; replace the nylock nuts every cycle.

50,000 miles

Serviced (date / mi):

- If the OEM water pump has been replaced with an aftermarket unit, replace it every 50k.

75,000 miles

Serviced (date / mi):

- Engine idler pulleys.
- Engine water pump - 50k miles after the initial change.
- Transmission fluid and filter - LR-recommended fluid for the normal interval, or Castrol Transynd full synthetic for a lifetime fill.

100,000 miles

Serviced (date / mi):

- All cooling system plastics, including the radiator fan.
- Radiator fan clutch.
- Brake master cylinder seal or master cylinder.
- Spark plugs - NGK 5553.

150,000 miles

Serviced (date / mi):

- Engine idler pulleys.
- Engine water pump.
- Transmission fluid - unless Transynd was used at the 75k service.

200,000 miles

Serviced (date / mi):

- Alternator.
- Starter.
- Power steering pump.
- Spark plugs - NGK 5553.
- Brake master cylinder seal or master cylinder.
- Radiator fan clutch.
- All cooling system plastics.